

EST-W6 Fire wall aesthetic speaker Power: 6W, 100V

Overview

The EST-W6 is an elegant multi-function loudspeaker designed to guarantee the highest acoustic parameters. Its solid casing offers an effective protection against acts of vandalism. The loudspeaker can be mounted either on a wall or on a ceiling. Additionally, the EST-W6 can be fixed as an recessed speaker and therefore it is an ideal solution for rooms where aesthetic factors play a significant role.

The loudspeaker offers adjustable power regulation through connectivity to applicable transformer tappings thus allowing suitable acoustic pressure (the level of sound) within areas of sound emission adequately to the acoustic conditions existing in those areas.



Details

- Certificate of Conformity issued by CNBOP: 1438-CPR-XXXX
- Compliance with BS5839-8 standard (Thermal protection)
- Exceptionally easy and quick to mount
- Modern and elegant design
- High quality sound of both speech and music
- · Ideal for on-wall or in-wall mounting

EST-W6


Fire wall aesthetic speaker Power: 6W, 100V

Technical specifications

Electrical		
Rated power	6 W	
Tappings 100 V line	6 / 3 / 1.5 / 0.75	
according to EN 54-24,		
W		
Tappings 70 V line, W	3 / 1.5 / 0.75 / 0.375	
	, 1667 / 3333 / 6667 / 13333	
Ω		
Driver impedance	8 Ω	
Effective frequency range	120-20 000 Hz	
Sensitivity at 4 m, 1 W	80 dB	
SPL at 4 m, Rated power	87 dB	
SPL at 1 m, 1 W, Test signal bandwith 300 Hz	94 dB	
SPL at 1 m, Rated power,101 dB Test signal bandwith 300 Hz - 6 katz		
Dispersion at 500 Hz / 1 kHz / 2 kHz / 4 kHz, [°]	180 / 180 / 163 / 80	
Physical		
Physical dimensions	260 x 180 x 80 mm (W x H x D)	
Net weight	2.3 kg	
Colour	White (RAL 9003)	
Housing material	Steel	
Mounting	Screw	
Optional for DC line monitoring	Capacitor	
Colour optional	RAL Palette	
Ease Model		
Environmental		
IP rating	32	
Environmental type / IP Rating according to EN 54-24	A / IP21C	
Min / Max Amb Temp	-10°C to +55°C	

Standards & regulation

Standards	EN54-24



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

