

SPB-2

Pluggable base for ZP755 devices

First fix wiring option

The SPB-2 pluggable base provides a basis for terminating ZP755 alarm device loop wiring at first fix stage. Forming an integral part of the overall unit assembly, the bases are provided with slots for screw fixing, either directly to the building structure, or a wide range of international conduit boxes. Bases feature large wiring terminals with captive clamping washers to ensure secure termination.

Robust manufacture

Bases are manufactured in moulded ABS and are available in either red or white.



Standard Features

- First fix facility
- Ease of installation
- Large wiring terminals



SPB-2

Pluggable base for ZP755 devices

Specifications

Model No	SPB-2W Pluggable base - white
	SPB-2R Pluggable base - red
Compatibility	ZP755 sounder beacon range
Mounting	Surface
Terminals	Loop +ve in/out
	Loop -ve in/out
	Cable screen continuity
	24 Vdc +ve external supply
	24 Vdc - ve external supply
Operating voltage	16 - 22 Vdc from panel
	24Vdc from external supply
Application	Indoor installation
Temperature range	-10°C to +75°C
Humidity range	20% to 95% RH (non condensing)
Material	Moulded ABS
Dimensions	127mm (Dia) x 5mm (H)
Colour	Red or white
Weight	61g

Ordering Information

Part No.	Description
----------	-------------